

EPOXY THINNER (NO.3)

THINNER FOR EPIREZ SUPATUFF HEAVY DUTY COATING (HD)



DESCRIPTION

EPIREZ® Epoxy Thinner (No.3) is used for thinning of EPIREZ Supatuff™ Heavy Duty Epoxy Coating (HD)

INTENDED USE

- Thinning EPIREZ® Supatuff™ Heavy Duty Epoxy Coating (HD)
- Cleaning of trowel, brushes

APPLICATION INSTRUCTIONS

Supatuff™ Heavy Duty Epoxy Coating (HD) can be applied by brush, roller or airless spray in two coats (minimum) to achieve 300 micron DFT. Thin first coat (if necessary) with up to 20% v/v Epiresz® Epoxy Thinner (No.3). Allow the coating to cure for 7 days prior to subjecting to chemical exposure.

Caution

- Care should be taken to avoid the solvent in contact with the skin.
- Epiresz® Epoxy Thinner (No.3) contains flammable solvent hence it should be kept away from naked flames, sparks etc.
- The lids of Epiresz® Epoxy Thinner (No.3) containers should be kept closed when not in use.
- Use gloves and half face masks while handling Epiresz® Epoxy Thinner (No.3).

STORAGE

Store in dry conditions between 10°C and 25°C, away from sources of heat and naked flames. Protect from frost. When stored in original sealed containers, the minimum shelf life is four years.

WARRANTY

Epiresz will replace any material found to be defective. Because the storage, handling and application of this material is beyond our control, we can accept no liability for the results obtained.

DISCLAIMER

All information on this data sheet is based on laboratory testing and is not intended for design purposes. ITW Polymers & Fluids and EPIREZ® makes no representations or warranties of any kind concerning this data.

ORDER INFORMATION

Item No.	Package Size
E993002	4Ltr
E993001	20Ltr

CONTACTS

ITW Polymers & Fluids
100 Hassall St Wetherill Park
NSW 2164 Australia
AU Phone: 1800 000 945
itwpf.com.au

ITW Polymers & Fluids
Unit 2 / 38 Trugood Drive
East Tamaki, 2013, Auckland, New Zealand
NZ Phone: 0800 476 265
itwpf.co.nz

EMERGENCY:

AU: 1800 033 111
NZ: 0800 734 607

For Health & Safety information, refer to Safety Data Sheet available from ITW Polymers & Fluids upon request or available on our website.